

SCOUR SUMMARY SHEET

Printed: 03/11/96

BR. NO: 91 WATERWAY: SOUTH SLOUGH SCOUR CODE: 8

OWNER: Sno. Co. SID: 08084500

Q₁₀₀: _____ cfs WATER SURFACE EL: _____ ft.

Q₅₀₀: _____ cfs WATER SURFACE EL: _____ ft.

SUPERSTRUCTURE LOW POINT (POINT OBSTRUCTS WATER FLOW) EL: _____ ft.

Q WHEN HIGH WATER TOUCHES BOTTOM OF BRIDGE (IF < Q₅₀₀): _____ cfs.

ANGLE OF ATTACK: 0 ° THALWEG ELEVATION: _____ ft.

VELOCITY: V₁₀₀ = 0.1 ft/sec ± V₅₀₀ = _____ ft/sec

CRITICAL PIER(S):

<u>PIER NUMBER</u>	<u>BOTTOM OF FOUNDATION ELEVATION</u>	<u>CALCULATED SCOUR ELEVATION</u>	<u>MONITOR² (U/W,R,F)</u>	<u>INSPECTION FREQUENCY²</u>
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____

- NOTE: 1. UNDER MONITOR ; U/W-UNDERWATER, R-ROUTINE, F-FATHOMETRIC
 2. MONITOR AND INSPECTION FREQUENCY - FILLED OUT BY WSDOT.
 3. ALL ELEVATIONS SHALL BE IN FEET.

MITIGATION: IN PLACE AND FUNCTIONING: N (Y/N)

DESC. OF MITIGATION: N/A

COMMENTS: "EXCLUDED" FROM SCOUR STUDY. BRIDGE IS (2) PCC LUTEN ARCHES END-TO-END (BUILT IN 1922) WATERWAY IS FLOOD RELIEF ONLY WITH NO SIGNIF. VELOCITY. BRIDGE WAS COMPLETELY SUBMERGED IN 1995 FLOOD (ALSO IN 1990) W/ NO SCOUR PROBLEMS (& NONE IN

FREQUENCIES (FILLED OUT BY BRIDGE SCOUR ENGINEER): OVER 70 YEARS

<u>TYPE OF INSPECTION</u>	<u>FREQUENCY (YEARS)</u>	<u>YEAR FREQ. ESTABLISHED</u>
STREAM CROSS SECTION U/S RAIL	_____	_____
UNDERWATER	_____	_____
FATHOMETRIC	_____	_____

DATE OF PHASE II ANALYSIS: ___/___/___

CONVENIENCE COPY

ANALYZED BY: (Signature) 8/29/96 B/C CONCUR: _____

BRIDGE PIER SCOUR EVALUATION

Date 6/15/92
 Agency Sno. Co. Bridge Number 91
 Bridge Name SOUTH SLOUGH
 Evaluated by G. Sawyer
 Superstructure type LUTEN ARCH

Superstructure Continuity?: Yes No Any Spread Footings?: Yes No

EVALUATION:

YES NO

Are foundation elevations known? If not, consider the bridge scour critical (using engineering judgment and any other information available).

Does the thalweg (the deepest portion of the stream; the main channel) meander back and forth across the floodplain? If so, the potential for a scour critical condition is increased.

For a spread footing, is the bottom of the seal (or footing, if the seal is not used) above the thalweg? If so, the bridge is scour critical; no need to proceed further.

For a pile supported footing, is the pile tip elevation 10 feet or less below the thalweg? If so the bridge is scour critical; no need to proceed further.

BRIDGE IS SCOUR CRITICAL YES NO EXCLUDED - FLOOD RELIEF CHANNEL ONLY - NORMALLY

EVALUATION CRITERIA:

ZERO FLOW

- Foundation elevations are (or are not) known and available.
- The thalweg meanders back and forth across the floodplain.
- Pier scour is always measured from the thalweg, even if the pier is in the overbank.
- For a spread footing, if the calculated depth of scour is below the footing, the bridge is scour critical.
- For a pile supported footing, if calculated depth of scour is 10' or less above pipe tip elevation, the bridge is scour critical.
- Scour should be calculated for 100 year flood. If not shown on bridge plan layout, check FEMA map. If not mapped by FEMA, use high water shown on layout.

CONVENIENCE COPY