

VALVE BOX AND EXTENSION

VALVE OPERATING NUT EXTENSION

NOTES:

- 1. VALVE OPERATING NUT EXTENSIONS ARE REQUIRED WHEN THE VALVE NUT IS MORE THAN THREE (3) FEET BELOW FINISHED GRADE. EXTENSIONS ARE TO BE A MINIMUM OF ONE (1) FOOT LONG. ONLY ONE EXTENSION WILL BE ALLOWED PER VALVE.
- 2. ALL VALVE OPERATING NUT EXTENSIONS ARE TO BE MADE OF STEEL, SIZED AS NOTED, AND PAINTED WITH TWO (2) COATS OF METAL PAINT.
- 3. VALVE BOXES SHALL BE CAST IRON, TWO PIECE UNITS, DESIGNED WITH DEEP SKIRT (2") LIDS W/LUGS, EQUAL TO "RICH NO. 940" AS MANUFACTURED BY RICH OR SATHER.
- 4. 4" THICK CONCRETE PAD AROUND VALVE BOXES OUTSIDE OF PAVED AREAS. 2'x2' SQUARE AROUND SINGLE VALVE BOXES AND 4'x4' AROUND MULTIPLE VALVE BOXES.

CUTYOF	APPROVED BY DATE	L. OLIVE 07/31/2008	DEPARTMENT OF PUBLIC WORKS STANDARD DETAILS	STANDARD DETAIL NUMBER
	REF STAD SPEC		VALVE BOX AND OPERATING NUT EXTENSION	
				W-190